

(43) International Publication Date 30 June 2005 (30.06.2005)

PCT

(10) International Publication Number WO 2005/059190 A1

(51) International Patent Classification7: C22C 9/00, 9/06

(21) International Application Number:

PCT/JP2004/018870

(22) International Filing Date:

10 December 2004 (10.12.2004)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data: 2003-419734

17 December 2003 (17.12.2003) J

(71) Applicant (for all designated States except US): TOY-OTA JIDOSHA KABUSHIKI KAISHA [JP/JP]; 1, Toyota-cho, Toyota-shi, Aichi, 4718571 (JP).

(72) Inventors; and

(75) Inventors/Applicants (for US only): KAWASAKI, Minoru [JP/JP]; c/o Toyota Jidosha Kabushiki Kaisha, 1, Toyota-cho, Toyota-shi, Aichi 4718571 (JP). OS-HIMA, Tadashi [JP/JP]; c/o Kabushiki Kaisha Toyota Chuo Kenkyusho, 41-1, Aza Yokomichi, Oaza Nagakute, Nagakute-cho, Aichi-gun, Aichi 4801192 (JP). KOBAYASHI, Takao [JP/JP]; c/o Kabushiki Kaisha Toyota Chuo Kenkyusho, 41-1, Aza Yokomichi, Oaza Nagakute, Nagakute-cho, Aichi-gun, Aichi 4801192 (JP).

NAKANISHI, Kazuyuki [JP/JP]; c/o Kabushiki Kaisha Toyota Chuo Kenkyusho, 41-1, Aza Yokomichi, Oaza Nagakute, Nagakute-cho, Aichi-gun, Aichi 4801192 (JP). TACHIKAWA, Hideo [JP/JP]; c/o Kabushiki Kaisha Toyota Chuo Kenkyusho, 41-1, Aza Yokomichi, Oaza Nagakute, Nagakute-cho, Aichi-gun, Aichi 4801192 (JP).

(74) Agent: OHKAWA, Hiroshi; 2-5, Meieki 3-chome, Nakamura-ku, Nagoya-shi, Aichi 4500002 (JP).


- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

with international search report

[Continued on next page]

(54) Title: WEAR-RESISTANT COPPER-BASED ALLOY



(57) Abstract: This aims to provide a wear-resistant copper-based alloy, which is advantages in not only enhancing wear resistance in a high temperature range but also enhancing crack resistance and machinability and which is especially suitable for forming a cladding layer. The wear-resistant copper-based alloy comprises, by weight, 4.7 to 22.0% nickel, 0.5 to 5.0% silicon, 2.7 to 22.0% iron, 1.0 to 15.0% chromium, 0.01 to 2.00% cobalt, 2.7 to 22.0% one or more of tantalum, titanium, zirconium and hafnium, and the balance of copper with inevitable impurities.

BEST AVAILABLE COPY

WO 2005/059190 A1

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

BEST AVAILABLE COPY